




**AK 3000/.. - 5,0 - slade grey**

**AK 3001/.. KD - 5,0 - slade grey**




**1-n poles, Spacing 5,0 mm adjustable to 5,08 mm insert required no. of poles ..**

**1-n poles, Spacing 5,0 mm adjustable to 5,08 mm insert required no. of poles ..**

**Ratings:**

			
	UL 1059	CSA 22.2 No. 158	EN 60998
<b>Rated Voltage</b>	<b>300 V</b>	<b>300 V</b>	<b>250 V</b>
<b>Rated Current</b>	<b>16 A</b>	<b>16 A</b>	<b>24 A (T60)</b>
<b>Wire Size</b>	<b>AWG 28-14</b>	<b>AWG 28-14</b>	<b>2,5 mm<sup>2</sup></b>
<b>Test Voltage</b>			<b>2,0 kV</b>
<b>Max. Rated Cross Section</b>			
Single Wire (solid)			<b>2,5 mm<sup>2</sup></b>
Stranded Wire (flexible)			<b>2,5 mm<sup>2</sup></b>
Stranded wire with Ferrules			<b>1,5 mm<sup>2</sup></b>

**Ratings:**

			
	UL 1059	CSA 22.2 No. 158	EN 60998
<b>Rated Voltage</b>	<b>300 V</b>	<b>300 V</b>	<b>250 V</b>
<b>Rated Current</b>	<b>16 A</b>	<b>16 A</b>	<b>24 A (T60)</b>
<b>Wire Size</b>	<b>AWG 28-14</b>	<b>AWG 28-14</b>	<b>2,5 mm<sup>2</sup></b>
<b>Test Voltage</b>			<b>2,0 kV</b>
<b>Max. Rated Cross Section</b>			
Single Wire (solid)			<b>2,5 mm<sup>2</sup></b>
Stranded Wire (flexible)			<b>2,5 mm<sup>2</sup></b>
Stranded wire with Ferrules			<b>1,5 mm<sup>2</sup></b>

**Dimensions**

Spacing	<b>5,0 mm (5,08 mm)</b>
PCB Hole Diameter	<b>1,0 mm (2x)</b>
Stripped Length	<b>6,0 mm</b>
<b>Materials</b>	
Insulating Material	<b>PA</b>
Flammability Class	<b>UL94 V-0</b>
Temperature Range	<b>-30°C/+105°C</b>
Cage clamp	<b>stainless steel</b>
Wire Guard	<b>Cu</b>
Colour	
slade grey	<b>RAL 7032</b>

**Dimensions**

Spacing	<b>5,0 mm (5,08 mm)</b>
PCB Hole Diameter	<b>1,0 mm (2x)</b>
Stripped Length	<b>6,0 mm</b>
<b>Materials</b>	
Insulating Material	<b>PA</b>
Flammability Class	<b>UL94 V-0</b>
Temperature Range	<b>-30°C/+105°C</b>
Cage clamp	<b>stainless steel</b>
Wire Guard	<b>Cu</b>
Colour	
slade grey	<b>RAL 7032</b>