



965 Series are new compact meters with double molded plastic housing and over sized high contrast 6000 counts LCD display. They are all CAT IV 600V/CATIII 1000V.

EMC & LVD
EN: 61326
EN: 61010-1
EN: 61010-02-032
EN: 61010-02-033



Specifications

Model	Range	DYNATEST	DYN965T
DC Voltage (V)	600mV/6V/60V/600V/1000V		±(0.5%+1)
AC Voltage (V)	600mV/6V/60V/600V/1000V		±(1.0%+3)
DC Current (A)	600µA/6000µA/60mA/600mA/6A/10A		±(1.0%+3)
AC Current (A)	600µA/6000µA/60mA/600mA/6A/10A		±(1.2%+3)
Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ		±(1.2%+5)
Capacitance (F)	60nF/600nF/6µF/60µF/600µF/6000µF		±(3.0%+5)
Frequency(Hz)	10Hz-10KHz		±(0.1%+5)
Temperature(°C)	-20°C~760°C		±(1.2%+3°C)
Temperature(°F)	-4°F~1400°F		±(2.0%+4°F)

Features

Display Count		6000
Auto Range		●
True RMS		●
Bandwidth(Hz)		45Hz-1kHz
Duty Cycle	0.1-99.9%	●
Diode		●
Auto Power Off	Around 15 Minutes	●
Continuity Buzzer		●
Low Battery Indication	≤4.5V	●
Data Hold/Relative Mode		●
MAX/MIN/AVG		MAX/MIN
Peak Value		●
Automatic backlight for LCD, Button, knob Switch & Flashlight		●
Analogue Bar Graph		61
Low input Impedance for DCV/ACV measurements	>3kΩ @ 600V MAX.	●
Input Protection		●
Input Impedance for DCV	Around 10MΩ	●
IP67 Waterproof		●

Size(HxWxD): 170mm x 74mm x 45mm
Weight: 218g

Accessories:
Test leads, 1.5AAA x 4 batteries, Temperature Probe, carrying case and gift box.

